

Which Table is right for you?

Surgical C-Arm Table - 840

Three-axis motorized positioning plus X-Y free-float



SPECIFICATIONS:

Dimensions:

Overall: 97" l x 26" w (246 x 66 cm) with OR accessory rails
 Tabletop: 97" l x 24" w (246 x 61 cm) – choice of classic contoured or rectangular design
 Catheter Tray Extension (removable): 18" l x 24" w (45.7 x 61 cm) non-radiolucent
 Radiolucent Area: 75" l x 24" w (191 x 61 cm)
 Tabletop Material: Carbon fiber with integral head section
 Mattress: Seamless, 2" thick (5 cm)
 Attenuation: 1.2 mm Aluminum equivalence

Motions:

Height Adjustable: 33.5" to 43.5" (84 to 109 cm)
 Tabletop X Motion (head-to-toe float): 35" (88.9 cm)
 Tabletop Y Motion (side-to-side float): 10" (25.4 cm)
 Trendelenburg: 0° to 20°
 Reverse Trendelenburg: 0° to 20°
 Isocentric Lateral Roll: 0° to ±15°

Controls:

Hand Control: activates height, isocentric lateral roll and Trendelenburg motions
 Foot Control: activates all motions (has release for float)
 Mushroom-Top Control: releases X-Y Tabletop motions

Accessory Rails: Standard OR accessory rails 49.5" x 1.12" x .375" (124 x 2.86 x .95 cm) mounted near foot end of table

Patient Restraints: Three body straps

Finish: Stainless Steel

Patient Capacity: 500 lb (227 kg)

Weight: 641 lb (291 kg)

Shipping Weight: 865 lb (392 kg)

Power: 115 VAC or 230 VAC and battery. Battery automatically charges when table is plugged in. An optional battery with separate charging unit provides continuous, cordless operation.

Certifications: ETL and cETL Listed to UL 60601-1@, CAN/CSA@ C22.2

No.: 601.1.M90, EN 60601-1, IEC 60601-2-46 and CE marked.

CDRH registered and FDA Device Listed

Warranty: **Two years parts and labor**

058-840 Table, Surgical C-Arm, Contour, 115V

058-840-10 Table, Surgical C-Arm, Rectangle, 115V

058-845 Table, Surgical C-Arm, Contour, 230V

058-845-10 Table, Surgical C-Arm, Rectangle, 230V

Surgical C-Arm Table - 846

Affordably priced float-top table



SPECIFICATIONS:

Dimensions:

Overall: 97" l x 26" w (246 x 66 cm) with OR accessory rails
 Tabletop: 97" l x 24" w (246 x 61 cm) – choice of classic contoured or rectangular design
 Radiolucent Area: 75" l x 24" w (191 x 61 cm)
 Tabletop Material: Carbon Fiber with integral head section
 Mattress: Seamless, 2" thick (5 cm)
 Attenuation: 1.2 mm Aluminum equivalence

Motions:

Height Adjustable from 32" to 42" (81 to 106 cm)
 Tabletop X Motion (head-to-toe float): 35" (89 cm)
 Tabletop Y Motion (side-to-side float): 10" (25.4 cm)

Controls:

Hand Control: activates height
 Mushroom-Top Control: releases X-Y Tabletop motions

Accessory Rails: Standard OR accessory rails 49.5" x 1.12" x .375" (124 x 2.86 x .95 cm) mounted near foot end of table

Patient Restraints: Three body straps

Finish: Stainless Steel

Patient Capacity: 500 lb (227 kg)

Shipping Weight: 800 lb (363 kg)

Power: 115 VAC or 230 VAC

Certifications: ETL and cETL listed to UL 60601-1@, CAN/CSA@ C22.2

No.: 601.1.M90, EN 60601-1, IEC 60601-2-46 and CE marked.

CDRH registered and FDA Device Listed

Warranty: **Two years parts and labor**

058-846 Table, Surgical C-Arm, Contour, 115V


058-846-10 Table, Surgical C-Arm, Rectangle, 115V

058-847 Table, Surgical C-Arm, Contour, 230V

058-847-10 Table, Surgical C-Arm, Rectangle, 230V

Pain Management C-Arm Table - 870

Ideal for pain care applications



SPECIFICATIONS:

Dimensions:

Overall: 97" l x 26" w (246 x 66 cm) with OR accessory rails
 Tabletop: 97" l x 24" w (246 x 61 cm) – choice of classic contoured or rectangular design
 Radiolucent Area: 70" l x 24" w (178 x 61 cm)
 Tabletop Material: Carbon fiber with integral head section
 Mattress: Seamless, 2" thick (5 cm)
 Attenuation: 1.2 mm Aluminum equivalence

Motions:

Height Adjustable: 29.5" to 39.5" (75 to 100 cm)
 Trendelenburg: 0° to 20°
 Reverse Trendelenburg: 0° to 20°
 Isocentric Lateral Roll: 15° clockwise or counterclockwise

Controls:

Hand Control: activates height, isocentric lateral roll and Trendelenburg motions
 Foot Control (optional): activates height, lateral roll and Trendelenburg motions

Accessory Rails: Standard OR accessory rails 30" x 1.12" x .375" (75 x 2.86 x .95 cm) mounted near foot end of table

Patient Restraints: Three body straps

Finish: Stainless Steel

Patient Capacity: 500 lb (227 kg)

Shipping Weight: 749 lb (340 kg)

Power: 115 VAC or 230 VAC

Certifications: ETL and cETL listed to UL 60601-1@, CAN/CSA@ C22.2

No.: 601.1.M90, EN 60601-1, IEC 60601-1-2, IEC 60601-2-46 and CE marked.

CDRH registered and FDA Device Listed

Warranty: **Two years parts and labor**

058-870 Table, Surgical C-Arm, Contour, 115V

058-870-10 Table, Surgical C-Arm, Rectangle, 115V

058-875 Table, Surgical C-Arm, Contour, 230V

058-875-10 Table, Surgical C-Arm, Rectangle, 230V

See pages 20-21 for Table Accessories, available separately.

Urology C-Arm Table - 800

Configure to your exact specifications



SPECIFICATIONS:

Dimensions: 84.5" l x 25.5" w (214.6 x 64.8 cm) with OR accessory rails
Tabletop: 53" l x 21" w (134.6 x 53.3 cm); 84" l (213.4 cm) with extension
Lightweight Extension (for patient transfer only, not for imaging): 26.5" l x 21" w (67.3 x 53.3 cm)
Radiolucent Extension: 31" l x 25.5" w (78.7 x 64.8 cm) with OR accessory rails
Radiolucent Area: 54" l x 17.5" w (137.2 x 44.5 cm)
Tabletop Material: Three Fibresin™ sections – each with individual 2" mattress
Mattress: Individual, seamless, 2" thick (5 cm), one for each section

Motions:

Height Adjustable: 34" to 43.5" (86.4 to 110.5 cm)
Tabletop X Motion (head-to-toe): 20" (51 cm)
Tabletop Y Motion (side-to-side): 10" (25.4 cm)
Trendelenburg: 0° to 20°
Reverse Trendelenburg: 0° to 20°
Lateral Roll: 0° to 20°
Fowler Positioning: Adjusts from 0° to 80° with touch handle lock/unlock

Controls:

Hand Control: activates all motions
Foot Control: activates all motions

Optional:

X-Ray Film Tray: Removable film cassette tray for 14" x 17" film with cassette mask for 10" x 12" film. Film cassette tray can be removed from either side of the table.
X-Ray Grid: Removable X-Ray grid, 103 line, 8:1 ratio
Accessory Rails: Standard OR accessory rails 1.125" x .375" (2.86 x .95 cm) on table (rails also on table imaging extension)
Patient Restraints: Two body straps, two ankle straps
Finish: Powder coat
Patient Capacity:
In urologic position: 500 lb (227 kg)
In use with radiolucent extension: 400 lb (181.4 kg)
Weight tested to four times the patient load rating.
Shipping Weight: 903 lb (409.6 kg)
Power: 115 VAC or 230 VAC and Battery. Battery automatically charges when table is plugged in. An additional battery can be charged with optional wall-mounted charger.
Certifications: ETL and cETL listed to UL-60601-1, CAN/CSA® C22.2
No.: 601.1.M90, EN 60601-1 and IEC- 60601-1-2:2001-09, CE marked.
CDRH registered and FDA Device Listed
Warranty: **Two years parts and labor**

058-800 Table, Urology C-Arm - 800, 115 VAC

058-805 Table, Urology C-Arm - 800, 230 VAC

Brachytherapy C-Arm Table - 810

For image-guided seed implantation



SPECIFICATIONS:

Dimensions: 84.5" l x 25.5" w (214.6 x 64.8 cm) with OR accessory rails
Tabletop: 53" l x 21" w (134.6 x 53.3 cm); 84" l (213.4 cm) with extension
Lightweight Extension (For patient transfer only, not for imaging): 26.5" l x 21" w (67.3 x 53.3 cm)
Radiolucent Extension: 31" l x 25.5" w (78.7 x 64.8 cm) with OR accessory rails
Radiolucent Area: 54" l x 17.5" w (137.2 x 44.5 cm)
Tabletop Material: Three Fibresin™ sections – each with individual 2" mattress
Mattress: Individual, seamless, 2" thick (5 cm), one for each section

Motions:

Height Adjustable: 34" to 43.5" (86.4 to 110.5 cm)
Tabletop X Motion (head-to-toe): 20" (51 cm)
Tabletop Y Motion (side-to-side): 10" (25.4 cm)
Trendelenburg: 0° to 20°
Reverse Trendelenburg: 0° to 20°
Lateral Roll: 0° to 20°
Fowler Positioning: Adjusts from 0° to 80° with touch handle lock/unlock

Controls:

Hand Control: activates all motions
Foot Control: activates all motions

Optional:

X-Ray Film Tray: Removable film cassette tray for 14" x 17" film with cassette mask for 10" x 12" film. Film cassette tray can be removed from either side of the table.
X-Ray Grid: Removable X-Ray grid, 103 line, 8:1 ratio
Accessory Rails: Standard OR accessory rails 1.125" x .375" (2.86 x .95 cm) on table (rails also on table imaging extension)
Patient Restraints: Two body straps, two ankle straps
Finish: Powder coat
Patient Capacity:
In urologic position: 500 lb (227 kg)
In use with radiolucent extension: 400 lb (181.4 kg)
Weight tested to four times the patient load rating.
Shipping Weight: 877 lb (398.6 kg)
Power: 115 VAC or 230 VAC and Battery. Battery automatically charges when table is plugged in. An additional battery can be charged with optional wall-mounted charger.
Certifications: ETL and cETL listed to UL-60601-1, CAN/CSA® C22.2
No.: 601.1.M90, EN 60601-1 and IEC- 60601-1-2:2001-09, CE marked.
CDRH registered and FDA Device Listed
Warranty: **Two years parts and labor**

058-810 Table, Brachytherapy - 810, 115 VAC

058-815 Table, Brachytherapy - 810, 230 VAC

3D Imaging C-Arm Table - 820

Designed to function with a 3D C-Arm



SPECIFICATIONS:

Dimensions: 103.75" l x 26" w (264 x 66 cm) with OR accessory rails
Tabletop: 103.75" l x 24" w (264 x 61 cm) includes head and leg extension
Radiolucent Area:
3D Imaging Area: 22.5" l x 24" w (57.1 x 61 cm)
Radiolucent Extension (Fibresin™, non-3D): 29" l x 22.5" w (73.6 x 57.1 cm)
Total Radiolucent Area (Combined): 51.5" l x 24" w (131 x 61 cm)
Head-End Extension (non viewable): 18.2" l x 24" w (46 x 51 cm)
Tabletop Material: Carbon fiber
Mattress: Vinyl covered, seamless, 2" thick (5 cm)

Motions:

Height Adjustable: 34" h to 44" h (86 to 112 cm)
Tabletop X Motion (head to toe): 10" (25 cm)
Tabletop Y Motion (side to side): 10" (25 cm)
Trendelenburg: 0° to 20°
Reverse Trendelenburg: 0° to 20°
Lateral Roll: 0° to 20°

Controls:

Hand Control: activates all motions
Foot Control: activates all motions

Accessory Rails: Standard OR accessory rails, 1.125" x .375" (2.86 x .95 cm). Head-End 30" l (75 cm); Foot-End 7.75" l (20 cm)
Patient Capacity: 500 lb (227 kg); weight tested to four times the patient load rating.
Power: 115 VAC or 230 VAC and Battery. Battery automatically charges when table is plugged in. An additional battery can be charged with optional wall-mounted charger.
Weight: 542 lb (246 kg)
Shipping Weight: 700 lb (318.1 kg)
Certifications: ETL and cETL listed to UL-60601-1, CAN/CSA® C22.2
No.: 601.1.M90, EN 60601-1 and IEC- 60601-1-2:2001-09, CE marked.
CDRH registered and FDA Device Listed
Warranty: **Two years parts and labor**

058-820 Table, 3D Imaging C-Arm, 115 VAC

058-825 Table, 3D Imaging C-Arm, 230 VAC

Because image is everything...